

NTN 4T-71437/71751D+A tapered roller bearings

Browse NTN 4T-71437/71751D+A tapered roller bearings 0.0 Inventory Categories N/A Minimum Buy Quantity in SKF Manufacturer Name the Manufacturers Online Free. including .

| | |
|--|-----------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 97.688 |
| EAN | 7316571680408 |
| Product Group | M06288 |
| inside diameter: | 170 mm, 6.9375 in |
| housing material: | Cast Iron |
| base to bore centerline: | 190 mm |
| compatible bearing type: | Spherical Roller |
| overall length: | 560 mm |
| finish/coating: | Uncoated |
| overall height: | 375 mm |
| compatible bearing series/part number: | 23138CCK/W33, C3138 K |
| overall width: | 260 mm |
| bolt center-to-center length: | 18.9 in |
| mounting: | Four-Bolt Base |
| base width: | 8.27 in |
| housing construction: | Split Pillow Block |
| series: | SNL |
| compatible bore diameter: | 170 mm, 6.9375 in |
| standards met: | ISO/DIS 185 Grade 200 |

| | |
|-----------------------------|---------------|
| Bearing (basic designation) | 22330 |
| Lock nut | KM 30 |
| Lock washer | MB 30 |
| Locating ring | 2 x FRB 8/320 |
| da | 150 mm |
| db | 170 mm |
| d2 | 300 mm |
| Ca | 124 mm |
| Da | 320 mm |
| A | 260 mm |
| A1 | 210 mm |
| ATS | 270 mm |
| ATK | 353 mm |
| H | 375 mm |
| H1 | 190 mm |
| H2 | 80 mm |
| J | 480 mm |
| J1 | 120 mm |
| L | 560 mm |
| N | 34 mm |
| N1 | 28 mm |
| s | 10 mm |
| ba min. | 85 mm |
| ba max. | 112 mm |
| bb | 80 mm |
| bc | 117.5 mm |
| J6 | 520 mm |
| N4 max. | 20 mm |
| Labyrinth seal | 2 x TS 38 |

| | |
|---|-----------|
| Taconite seal | 2 x TK 38 |
| End cover | ETS 38 |
| P0° | 2200 kN |
| P55° | 2700 kN |
| P90° | 1300 kN |
| P120° | 1000 kN |
| P150° | 880 kN |
| P180° | 1100 kN |
| Pa | 710 kN |
| Q120° | 1800 kN |
| Q150° | 1040 kN |
| Q180° | 900 kN |
| Mass housing | 97.5 kg |
| Cap bolt, size | M 24×150 |
| Cap bolt, rec. tightening torque | 350 N·m |
| Appropriate attachment bolt, size G | 24 mm |
| Appropriate attachment bolt, rec. tightening torque | 665 N·m |
| Eye bolt, size | 2 x M 20 |
| Initial grease fill, 20% | 1.2 kg |
| Initial grease fill, 40% | 1.8 kg |
| Adapter sleeve | HA 3138 |