

NTN 4T-782/772 tapered roller bearings

What are 6 RoHS the 6 Days or more Days to Ship dimensions of a NTN 4T-782/772 tapered roller bearings? Manufacturing Service . Get Your Free, Instant Quote

Days to Ship	6 Days or more
RoHS	6
Type	Angular Contact Ball Bearing (Single Row)
Precision	Grade 0
d	17
D	40
B	12
Basic Dynamic Load Rating(N)	11000
Max. Allowed rpm(rpm)	17000
Specifications/Environment	Standard
Load Direction	Radial
Number of Raceway Ring Rows	Single Row
Retainer Type	Punching
Types	7*** series
Contact angle symbol	B
Inner/Outer Ring Material	Steel
Bearing Style	Open Type
Outer Ring Shape	Flat
Size Standards	Metric System
Rolling Element Material	Steel

I.D.(Ø)	17
O.D.(Ø)	40
Width(mm)	12
Specifications, Environment	Standard
Combination of Angular Contact Ball Bearings	Single Row
Basic Load Rating, Static Rating(N)	5500
Clearance sign	CN (standard)
Preload	Normal preload
Contact angle(Degree)	40
Holder Symbol	No
Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	No
Precision Grade Symbol	No
Symbol of contact angle	B
Combination symbol	No
Preload Mark	No
Special Configurations Code	No
Bearing type symbol	No
Type symbol	No
Outer Ring	With Outer Ring