

# NTN 4T-82587/J82945 tapered roller bearings

What are the dimensions N/A Minimum Buy Quantity of a NTN 4T-82587/J82945 tapered roller bearings? Manufacturing Service . Get SKF Manufacturer Name Your Free, 0.0 Inventory Instant Quote

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | SKF   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 9.53  |
| EAN                       | 7316577026361                                       |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar                                   |
| Housing Style             | 2 Bolt Pillow Block                                 |
| Rolling Element           | Spherical Roller Bearing                            |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22215   |
| Seals                     | Labyrinth   |
| Housing Configuration     | 1 Piece Solid                                       |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Heavy Duty   Open End   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 2-15/16" Bore; 3-1/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | SYR 2.15/16-18   |
| Weight / LBS                  | 21   |
| D                             | 3.625 Inch   92.075 Millimeter   |
| B                             | 3.25 Inch   82.55 Millimeter   |
| Bolt Spacing Minimum          | 7.813 Inch   198.44Millimeter  |
| d                             | 2.938 Inch   74.625 Millimeter   |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter  |
| Bolt Spacing Maximum          | 8.438 Inch   214.325Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| bore diameter:                | 2.9375 in  |
| expansion type:               | Expansion Bearing (Floating)   |
| overall length:               | 10.4375 in   |
| finish/coating:               | Uncoated   |
| overall height:               | 6.4375 in  |
| overall width:                | 3-11/16 in   |
| mounting:                     | Two-Bolt Base  |
| seal type:                    | Labyrinth  |
| bearing type:                 | Spherical Roller   |
| radial dynamic load capacity: | 35500 lbf  |
| bore type:                    | Round  |
| radial static load capacity:  | 46800 lbf  |
| housing construction:         | Solid Pillow Block   |

|                               |                      |
|-------------------------------|----------------------|
| maximum rpm:                  | 2800 RPM             |
| base to bore centerline:      | 3.2500 in            |
| lubrication type:             | Lubrication Fitting  |
| housing material:             | Cast Iron            |
| end type:                     | Open                 |
| locking device:               | Concentric Collar    |
| series:                       | SYR                  |
| bolt center-to-center length: | 7-13/16 to 8-7/16 in |
| replacement bearing:          | 22215                |
| base width:                   | 2-11/16 in           |