

# NTN 4T-95525/95925 tapered roller bearings

100% Authentic. NTN 4T-95525/95925 tapered roller bearings 20x42x25 Size (mm) Highest Quality. Certified Supplier.

Size (mm)	20x42x25
Bore Diameter (mm)	20
Outer Diameter (mm)	42
Width (mm)	25
d	20 mm
D	42 mm
B	25 mm
C	16 mm
$\alpha$	17 °
dk	35.5 mm
b	3.1 mm
b1	3.1 mm
M	2 mm
r1 – min.	0.3 mm
r2 – min.	0.6 mm
da – min.	22.7 mm
da – max.	25.2 mm
Da – min.	36.9 mm
Da – max.	39.2 mm
ra – max.	0.3 mm
rb – max.	0.6 mm
Basic dynamic load rating – C	72 kN
Basic static load rating – C0	240 kN

Specific factor dynamic load – K	150 N/mm <sup>2</sup>
Specific factor static load – K <sub>0</sub>	500 N/mm <sup>2</sup>
Constant – K <sub>M</sub>	330
Lubricant	Maintenance free – greased for life
Design (sliding contact surface combination)	Steel/steel
Sealing solution	Triple-lip seals
$\alpha$	17 °
r <sub>1</sub> min.	0.3 mm
r <sub>2</sub> min.	0.6 mm
d <sub>a</sub> min.	22.7 mm
d <sub>a</sub> max.	25.2 mm
D <sub>a</sub> min.	36.9 mm
D <sub>a</sub> max.	39.2 mm
r <sub>a</sub> max.	0.3 mm
r <sub>b</sub> max.	0.6 mm
Basic dynamic load rating C	72 kN
Basic static load rating C <sub>0</sub>	240 kN
Specific dynamic load factor K	150 N/mm <sup>2</sup>
Specific static load factor K <sub>0</sub>	500 N/mm <sup>2</sup>
Material constant K <sub>M</sub>	330
Mass plain bearing	0.16 kg