

NTN 4T-CR-1084PX1 tapered roller bearings

NTN 4T-CR-1084PX1 tapered roller bearings
 1308.1×1004.634×812.8 Size (mm) Manufacturers , Online
 Wholesale Suppliers !

Size (mm)	1308.1×1004.634×812.8
Bore Diameter (mm)	1308,1
Outer Diameter (mm)	1004,634
Width (mm)	812,8
d	1004.634 mm
D	1308.1 mm
B	812.8 mm
T	730.25 mm
r _{3,4} – min.	3.3 mm
Basic dynamic load rating – C	24600 kN
Basic static load rating – C ₀	76500 kN
Fatigue load limit – P _u	4400 kN
Comparative radial load rating – C _F	6550 kN
Comparative axial load rating – C _{Fa}	1080 kN
Thrust factor – K	1.76
Calculation factor – e	0.33
Calculation factor – Y ₁	2
Calculation factor – Y ₂	3
Calculation factor – Y ₀	2
Mass bearing	3060 kg
Design variant/feature	TQIT.1
d ₁ ≈	1135 mm

D1 ≈	1260 mm
r1,2 min.	12.7 mm
r3,4 min.	3.3 mm
Basic dynamic load rating C	24600 kN
Basic static load rating C0	76500 kN
Fatigue load limit Pu	4400 kN
Comparative radial load rating CF	6550 kN
Comparative axial load rating CFa	1080 kN
Thrust factor K	1.76
Calculation factor e	0.33
Calculation factor Y1	2
Calculation factor Y2	3
Calculation factor Y0	2