

# NTN 4T-CRI0821 tapered roller bearings

Browse NTN 4T-CRI0821 tapered roller bearings Categories in the Manufacturers Online Free. 560 Outer Diameter (mm) including 680x560x45 Size (mm) .

Size (mm)	680x560x45
Bore Diameter (mm)	680
Outer Diameter (mm)	560
Width (mm)	45
d	560 mm
D	680 mm
B	45 mm
d1	606 mm
D1	638 mm
E	645 mm
r1,2 – min.	3 mm
s	8.2 mm
da – min.	573 mm
Da – max.	667 mm
Db – min.	647 mm
ra – max.	2.5 mm
Basic dynamic load rating – C	429 kN
Basic static load rating – C0	950 kN
Fatigue load limit – Pu	62 kN
Reference speed	2000 r/min
Limiting speed	3200 r/min
Calculation factor – kr	0.02

d1 ≈	606 mm
D1 ≈	638 mm
r1,2 min.	3 mm
s max.	8.2 mm
da min.	573 mm
Da max.	667 mm
Db min.	647 mm
ra max.	2.5 mm
Basic dynamic load rating C	429 kN
Basic static load rating C0	950 kN
Fatigue load limit Pu	62 kN
Calculation factor kr	0.02
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	32 kg