

NTN 4T-LM522549/LM522510 tapered roller bearings

Offer 140x210x33 Size (mm) High Quality Brand NTN 4T-LM522549/LM522510 tapered roller bearings .Contact Us Online to Get Best Quote.

Size (mm)	140x210x33
Bore Diameter (mm)	140
Outer Diameter (mm)	210
Width (mm)	33
d	140 mm
D	210 mm
B	33 mm
C	33 mm
Angle (α)	30 °
a	34 mm
r min.	2 mm
r1 min.	1 mm
2B	66 mm
da min.	148 mm
Da max.	205 mm
ra max.	1 mm
Weight	3.63 Kg
Basic dynamic load rating (C)	194 kN
Basic static load rating (C0)	265 kN
(Grease) Lubrication Speed	1900 r/min
Bore Type	Cylindrical Bore
Enclosure	Open

Configuration	Duplex
Bore Size	140 mm
Outside Diameter	210 mm
Width	33 mm
Fillet Radius/Chamfer	2 mm
r1	1 mm
Dynamic Load Rating	194,000 N
Static Load Rating	265,000 N
Limiting Speed – Grease	1,900 rpm
Limiting Speed – Oil	2,600 rpm
da1 (min)	148 mm
da2 (min)	148 mm
Da1 (max)	202 mm
Da2 (max)	205 mm
ra (max)	2 mm
ra1 (max)	1 mm