

NTN 4T-NA48390/48320D tapered roller bearings

What is NTN 4T-NA48390/48320D tapered roller bearings in mechanical engineering? 30 Outer Diameter (mm) Manufacturing Service . Upload your CAD file for an 55x30x13 Size (mm) instant.

Size (mm)	55x30x13
Bore Diameter (mm)	55
Outer Diameter (mm)	30
Width (mm)	13
d	30 mm
D	55 mm
B	13 mm
d1	38.2 mm
D2	49 mm
r1,2 – min.	1 mm
da – min.	34.6 mm
da – max.	38.1 mm
Da – max.	50.4 mm
ra – max.	1 mm
Basic dynamic load rating – C	13.8 kN
Basic static load rating – C0	8.3 kN
Fatigue load limit – Pu	0.355 kN
Limiting speed	8000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	15
Inventory	6.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.126
EAN	7316571408019
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 55MM Outside Diameter; 13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6006-2RS1
Weight / LBS	0.278
Bore	1.181 Inch 30 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Outside Diameter	2.165 Inch 55 Millimeter

bore diameter:	30 mm
static load capacity:	8.3 kN
outside diameter:	55 mm
precision rating:	Not Rated
overall width:	13 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
outer ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
internal clearance:	C0
maximum rpm:	8000 RPM
operating temperature range:	-40 to +210 °F
series:	60
dynamic load capacity:	13.8 kN
d1 ≈	38.2 mm
D2 ≈	49 mm
r1,2 min.	1 mm
da min.	34.6 mm
da max.	38.1 mm
Da max.	50.4 mm
ra max.	1 mm
Basic dynamic load rating C	13.8 kN
Basic static load rating C0	8.3 kN
Fatigue load limit Pu	0.355 kN
Calculation factor kr	0.025
Calculation factor f0	15

Mass bearing	0.12 kg
--------------	---------