

# NTN 5S-2LA-HSE911ADG/GNP42 angular contact ball bearings

What 165.1 mm da is the best place to buy NTN 5S-2LA-HSE911ADG/GNP42 angular contact ball bearings online?  
Manufacturing Service . 279.999 mm Da

|                         |                |
|-------------------------|----------------|
| da                      | 165.1 mm       |
| Da                      | 279.999 mm     |
| Ca                      | 102.794 mm     |
| A1                      | 158.75 mm      |
| A2                      | 222.25 mm      |
| ba                      | 68.263 mm      |
| H                       | 336.55 mm      |
| H1                      | 169.875 mm     |
| H2                      | 66.675 mm      |
| J min.                  | 441.325 mm     |
| J max.                  | 488.95 mm      |
| J1                      | 95.25 mm       |
| L                       | 558.8 mm       |
| N1                      | 28.575 mm      |
| R1                      | 104.775 mm     |
| R2                      | 33.337 mm      |
| RG                      | 3/4 NPT        |
| PG                      | 1/4 NPT        |
| h                       | 52.388 mm      |
| Housing                 | SAF 036 KA     |
| Bearing                 | 23036 CCK/W33  |
| Adapter sleeve assembly | SNW 3036×6.1/2 |

|  |                |
|--|----------------|
| Stabilizing ring                       | 2 x 38151-36   |
| Labyrinth ring                         | 2 x LOR 146    |
| End plug (suffix Y)                    | EPR 19         |
| Bearing limiting speed                 | 2600 r/min     |
| P60°                                   | 226 kN         |
| P90°                                   | 136 kN         |
| P120°                                  | 85.9 kN        |
| P150°                                  | 78.3 kN        |
| P180°                                  | 94.3 kN        |
| Pa                                     | 40 kN          |
| Mass pillow block                      | 94.8 kg        |
| Cap bolt                               | 4 x 3/4-10 UNC |
| Cap bolt recommended tightening torque | 203.4 N·m      |
| Cap bolt, SAE grade                    | 5              |
| Eye bolt                               | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G     | 1 in           |
| Initial grease fill                    | 793.8 g        |