

NTN 5S-2LA-HSE930ADG/GNP42 angular contact ball bearings

LET OUR NTN 5S-2LA-HSE930ADG/GNP42 angular contact ball bearings EXPERTS GET 168.275 mm db YOU THE 150 mm da PARTS YOU NEED.

da	150 mm
db	168.275 mm
dc	146.05 mm
Da	269.999 mm
Ca	82.804 mm
A1	158.75 mm
A2	279.4 mm
S	4.763 mm
ba	65.088 mm
H	320.675 mm
H1	160.325 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/4 NPT
PG	1/4 NPT
h	50.8 mm

Housing	SAF 230
Bearing	22230 CC/W33
Lock nut	AN 30
Lock washer	W 30
Stabilizing ring	SR-30-0
Taconite seal (db shaft position)	TER 151
Taconite seal (dc shaft position)	TER 134
End plug (suffix Y)	EPR 17
Max. speed for Taconite seal	460 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	62.3 kN
Mass pillow block	82.3 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g