

NTN 5S-7902UADG/GNP42 angular contact ball bearings

Advance NTN 5S-7902UADG/GNP42 angular contact ball bearings is your source for quality 36 Outer Diameter (mm) and accessories. shop thrust washer Bearing Type online for home delivery or pick up in one of our 18 Bore Diameter (mm) 10000 .

Bore Diameter (mm)	18
Outer Diameter (mm)	36
Bearing Type	thrust washer
Shaft Dia., Nominal (d)	18.0000
Bearing Outside Diameter, Nominal(Do)	36.000
Washer Inside Diameter, Nominal (di)	20
Washer Inside Diameter Tolerance (di tol.) – +0.25 / -0.0	+0.25 / 0.0
Washer Outside Diameter, Nominal (Do)	36
Washer Outside Diameter Tolerance (Do tol.) – +0.0 / -0.25	+0.0 / 0.25
Washer Thickness, Nominal (S3)	2
Washer Thickness Tolerance (S3 tol.) – +0.0 / -0.05	+0.0 / 0.05
Mounting Hole Dia. (dm)	3.000
Mounting Hole Pitch Dia. (dp)	28
Housing Counterbore Depth (Ha)	1.00
Housing Counterbore Depth Tolerance (Ha tol.) – +0.2 / -0.2	+0.2 / 0.2
Housing Counterbore Diameter, Nominal (HD)	36.000

Housing Counterbore Diameter Tolerance (HD tol.) – +0.12 / -0.0	+0.12 / 0.0
Material	Molded plastic with self lubricating resins.