

# NTN 5S-7908UCG/GNP42 angular contact ball bearings

What is the best 80 Bore Diameter (mm) place to buy 140 Outer Diameter (mm) NTN 5S-7908UCG/GNP42 angular contact ball bearings online? Manufacturing Service 80x140x26 Size (mm) .

Size (mm)	80x140x26
Bore Diameter (mm)	80
Outer Diameter (mm)	140
Width (mm)	26
d	80 mm
D	140 mm
B	26 mm
C	26 mm
r min.	2 mm
da min.	89 mm
da max	95,5 mm
Da max.	131 mm
ra max.	2 mm
Weight	1,4 Kg
Basic dynamic load rating (C)	72,5 kN
Basic static load rating (C0)	53 kN
Reference speed	3 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359005035

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	80MM Bore; 140MM Outside Diameter; 26MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricat
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	3.09
Outside Diameter	5.512 Inch   140 Millimeter
Outer Race Width	1.024 Inch   26 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore	3.15 Inch   80 Millimeter
bore diameter:	80 mm
static load capacity:	53000 N

outside diameter:	140 mm
precision rating:	ISO Class 0
overall width:	26 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	26 mm
snap ring included:	Without Snap Ring
outer ring width:	26 mm
internal clearance:	CN
maximum rpm (grease):	3000 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	2 mm
dynamic load capacity:	72500 N
manufacturer product page:	<a href="#">Click here</a>