

NTN 6208LH deep groove ball bearings

What are the N/A Minimum Buy Quantity types 0.0 Inventory of NTN 6208LH deep groove ball bearings ? Manufacturing Service . Get Your Free, Instant price, design review.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	29.96
EAN	7316576668265
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Tapered Adapter Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	1316 K
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Double Row Medium Duty
Long Description	2 Bolt Pillow Block; 2-11/16" Bore; 4-1/4" Base to Center Height; Tapered Adapter Sleeve M

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 1616
Weight / LBS	66
Bolt Spacing Minimum	10.625 Inch 269.875Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
D	6.5 Inch 165.1 Millimeter
Bolt Spacing Maximum	12.625 Inch 320.675Millimeter
d	2.688 Inch 68.275 Millimeter
B	4.25 Inch 107.95 Millimeter
Nominal Bolt Center to Center	11.6 Inch 294.6 Millimeter
da	68.263 mm
Da	170 mm
Ca	67.793 mm
A1	98.425 mm
A2	160.338 mm
ba	36.513 mm
H	209.55 mm
H1	107.95 mm
H2	44.45 mm
J min.	269.875 mm
J max.	320.675 mm
L	361.95 mm
N1	22.225 mm
R1	63.5 mm
R2	26.988 mm

RG	3/8 NPT
PG	1/8 NPT
h	46.038 mm
Housing	SAF 616
Bearing	1316 K
Adapter sleeve assembly	SNW 16×2.11/16
Stabilizing ring	2 x SR-1616
Labyrinth ring	2 x LOR 44
End plug (suffix Y)	EPR 8
Bearing limiting speed	5300 r/min
P60°	85.9 kN
P90°	51.6 kN
P120°	32 kN
P150°	28.9 kN
P180°	34.7 kN
Pa	9.43 kN
Mass pillow block	29.8 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	365.71 g