

NTN 6218LLU deep groove ball bearings

Offer High Quality Brand NTN 6218LLU deep groove ball bearings .Contact Us Online to Get Best Quote. 133.35 mm da

da	133.35 mm
Da	319.999 mm
Ca	117.805 mm
A1	180.975 mm
A2	317.5 mm
S	4.763 mm
ba	83.344 mm
H	377.825 mm
H1	190.5 mm
H2	76.2 mm
J min.	530.225 mm
J max.	600.075 mm
J1	117.475 mm
L	679.45 mm
N1	28.575 mm
R1	114.3 mm
R2	41.275 mm
RG	3/4 NPT
PG	1/4 NPT
h	66.675 mm
Housing	SAF 630
Bearing	22330 CCK/W33
Adapter sleeve assembly	SNW 130×5.1/4

Stabilizing ring	SR-36-30
Taconite seal	TER 126
End plug (suffix Y)	EPR 17
Max. speed for Taconite seal	590 r/min
P60°	234 kN
P90°	140 kN
P120°	84.5 kN
P150°	75.6 kN
P180°	89 kN
Pa	48.9 kN
Mass pillow block	146 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	1304.1 g