

# NTN 7000UADG/GNP42 angular contact ball bearings

100% Authentic. NTN 7000UADG/GNP42 angular contact ball bearings Highest Quality. 0.0 Inventory TIMKEN Manufacturer Name Certified Supplier.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	42 lb
EAN	0053893778655
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only – Half Round Top Angle
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row   Double Collar   Two Lip Seal   Electrodeposition Coating   With Set Screw
Inch – Metric	Metric
Long Description	Take Up Bearing Only; 85MM Bore; Tapered Roller Bearing; Unit Only – Half Round Top Angle; Concentri
UNSPSC	31171533
Harmonized Tariff Code	8483.20.40.80

Noun	Bearing
Keyword String	Take Up
Manufacturer Item Number	E-TTU-TRB-85MM
Weight / LBS	44.84
Slot Width	0 Inch   0 Millimeter
d	3.346 Inch   85 Millimeter
Slot to Slot Distance	0 Inch   0 Millimeter
Shaft Size	3.346 in
Shaft Size Type	Metric
UPC Code	053893778655
Dimension B	5 in
Dimension H	9-5/8 in
Dimension H1	8-5/16 in
Dimension H2	4.05 in
Dimension d1	5-17/32 in
Dimension A	2-1/2 in
Dimension A1	2-1/2 in
Housing Width	3-1/2 in
Dimension L	9-1/2 in
Dimension L1	9 in
Dimension L2	4.46 in
e	0.50
X (if $F_a/F_r \leq e$ )	0.87
Y (if $F_a/F_r \leq e$ )	1.71
X (if $F_a/F_r > e$ )	0.7
Y (if $F_a/F_r > e$ )	2.07
K Factor	1.19
C90 Dynamic Load Rating <sub>1</sub>	19600 lb
C0 Static Load Rating	108600 lb

Fa-max Maximum Permissible Thrust Load <sup>2</sup>	5181 lb
Fr-max Maximum Allowable Slip Fit Radial Load <sup>3</sup>	16000 lb
Max. Speed <sup>4</sup>	1640 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to