

NTN 7016CG/GNP4 angular contact ball bearings

offers a 0.0 Inventory NTN 7016CG/GNP4 angular contact ball bearings N/A Minimum Buy Quantity selection of Genuine at Wholesale Prices. We are a NTN 7016CG/GNP4 angular contact ball bearings Certified Parts Retailer

| | |
|---------------------------|-------------------------------------------------------------------------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight | 9.01 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | Brass |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | Inner Ring – Both Sides |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Standard Capacity Plain Inner Ring 2 Rib Outer Ring Medium Series Cage on Outer Ring ID |

| | |
|--------------------------|-----------------------------------------------------------------------------------------------------|
| Long Description | 100MM Bore; Straight Bore Profile; 215MM Outside Diameter; 47MM Width; Brass Cage Matetrial; RBEC 1 |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer Item Number | NU320M |
| Weight / LBS | 19.841 |
| D | 8.465 Inch 215 Millimeter |
| d | 100 |
| B | 1.85 Inch 47 Millimeter |
| hidYobi | NU320M |
| LangID | 1 |
| D_ | 215 |
| C | 315 |
| B_ | 47 |
| hidTable | ecat_NSCLDR |
| Oil rpm | 3400 |
| rb | 2.5 |
| mass | 8.65 |
| GRS rpm | 2800 |
| ra | 2.5 |
| db max | 126 |
| TSR rpm | 3800 |
| C0 | 365 |
| DE_ | 185.5 |
| Prod_Type3 | CRB_SR_NU |
| da | 113 |
| DA_ | 28 |

| | |
|---------|--------|
| Z_ | 14 |
| D_a max | 202 |
| yobi | NU320M |
| dd min | 143 |
| Fw | 129.5 |
| C_conv | 315000 |
| ALPHA_ | 0 |
| SDM_ | 157.5 |
| r | 3 |
| db min | 113 |
| dc min | 132 |
| KBRG | 4144 |
| SBRG | 3 |
| r1 | 3 |
| DI_ | 129.5 |