

# NTN 7210BG angular contact ball bearings

NTN 7210BG angular contact ball bearings Deal is your source for OEM and accessories. We sell Genuine at discount prices. 15000 Series

|   |               |
|---|---------------|
| Series  | 15000         |
| Cone Part Number  | 15116         |
| Cup Part Number   | 15249         |
| Design Units  | Imperial      |
| Bearing Weight  | 0.30 Kg       |
| Cage Type   | Stamped Steel |
| d   | 30.112 mm     |
| D   | 63.500 mm     |
| B – Cone Width  | 20.638 mm     |
| C – Cup Width   | 15.875 mm     |
| B   | 20.638 mm     |
| R – Cone Backface To Clear Radius <sup>1</sup>                    | 0.760 mm      |
| r – Cup Backface To Clear Radius <sup>2</sup>                     | 1.52 mm       |
| da – Cone Frontface Backing Diameter                              | 35.56 mm      |
| db – Cone Backface Backing Diameter                               | 36.07 mm      |
| Da – Cup Frontface Backing Diameter                               | 59.44 mm      |
| Db – Cup Backface Backing Diameter                                | 55.12 mm      |
| Ab – Cage-Cone Frontface Clearance                                | 1.8 mm        |
| Aa – Cage-Cone Backface Clearance                                 | 0.8 mm        |
| a – Effective Center Location <sup>3</sup>                        | -5.8 mm       |
| C90 – Dynamic Radial Rating (90 million revolutions) <sup>4</sup> | 3490 lbf      |

|  |           |
|--|-----------|
| C1 – Dynamic Radial Rating (1 million revolutions) <sup>5</sup>    | 13500 lbf |
| C0 – Static Radial Rating  | 12100 lbf |
| Ca90 – Dynamic Thrust Rating (90 million revolutions) <sup>6</sup> | 2090 lbf  |
| K – Factor <sup>7</sup>  | 1.67      |
| e – ISO Factor <sup>8</sup>  | 0.35      |
| Y – ISO Factor <sup>9</sup>  | 1.71      |
| G1 – Heat Generation Factor (Roller-Raceway)                       | 14.6      |
| G2 – Heat Generation Factor (Rib-Roller End)                       | 10        |
| Cg – Geometry Factor   | 0.0606    |