

# NTN 7313BG angular contact ball bearings

How do I place an EMERGENCY 0.0 Inventory order for a NTN 7313BG angular contact ball bearings that I want to pick N/A Minimum Buy Quantity up at a our store?

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 5.448  |
| EAN                       | 0883450007634  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22211  |
| Seals                     | Double Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Heavy Duty  |
| Long Description          | 2 Bolt Pillow Block; 1-15/16" Bore; 2-1/4" Base to Center Height; Tapered Adapter Sleeve M |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | DVP11K115SC                    |
| Weight / LBS                  | 13                             |
| Bolt Spacing Maximum          | 7.125 Inch   180.975Millimeter |
| Nominal Bolt Center to Center | 6.6 Inch   167 Millimeter      |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| B                             | 2.25 Inch   57.15 Millimeter   |
| D                             | 2.32 Inch   58.928 Millimeter  |
| Bolt Spacing Minimum          | 6 Inch   152.4Millimeter       |
| d                             | 1.938 Inch   49.225 Millimeter |