

# NTN 7904UCGD2/GLP4 angular contact ball bearings

What is NTN 7904UCGD2/GLP4 angular contact ball bearings in mechanical engineering? 89.789 mm Ca Manufacturing Service . Upload your 289.999 mm Da CAD file for 176.213 mm da an instant.

da	176.213 mm
Da	289.999 mm
Ca	89.789 mm
A1	158.75 mm
A2	288.925 mm
ba	69.85 mm
H	338.137 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	47.625 mm
Housing	SAFS 038 KA
Bearing	23038 CCK/W33

Adapter sleeve assembly	SNW 3038×6.15/16
Stabilizing ring	2 x 38151-38
Taconite seal	TER 155
End plug (suffix Y)	EPR 21
Max. speed for Taconite seal	440 r/min
P60°	345 kN
P90°	207 kN
P120°	133 kN
P150°	120 kN
P180°	145 kN
Pa	42.9 kN
Mass pillow block	121 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g