

# NTN 7906UCG/GNP4 angular contact ball bearings

Can't find what you're looking 77.8 mm Ca for NTN 7906UCG/GNP4 angular contact ball bearings ? Our expert Representatives be in contact 127 mm da with you shortly!

da	127 mm
Da	250 mm
Ca	77.8 mm
A1	149.225 mm
A2	193.675 mm
S	4.763 mm
ba	61.119 mm
H	298.45 mm
H1	152.4 mm
H2	60.325 mm
L	511.175 mm
R1	87.313 mm
R2	38.1 mm
RG	3/4 NPT
PG	1/4 NPT
h	51.594 mm
Housing	SSAFS 528
Bearing	22228 CCK/W33
Adapter sleeve assembly	SNW 28×5
Stabilizing ring	SR-28-0
Labyrinth ring	2 x LOR 123
PosiTrac Plus contact element	2 x B10724-122

End plug (suffix Y)	EPR 27
Max. speed for PosiTrac Plus seal	1150 r/min
P60°	301 kN
P90°	180 kN
P120°	116 kN
P150°	105 kN
P180°	127 kN
Pa	28.5 kN
Mass pillow block	94.3 kg
Cap bolt	3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	481.95 g