

# NTN 7911DT angular contact ball bearings

Advance NTN 7911DT angular contact ball bearings is your source for quality and accessories. shop online for N/A Minimum Buy Quantity home delivery or pick up in 0.0 Inventory one of our 10000 .

|                            |   |
|----------------------------|---|
| Inventory                  | 0.0   |
| Manufacturer Name          | NTN   |
| Minimum Buy Quantity       | N/A   |
| Weight                     | 0.054   |
| EAN                        | 4547359290226   |
| Product Group              | B00308  |
| Rolling Element            | Ball Bearing  |
| Thrust Bearing             | Yes   |
| Single or Double Direction | Single Direction  |
| Banded                     | No  |
| Cage Material              | Steel   |
| Precision Class            | ABEC 1   ISO P0   |
| Component Description      | Roller Assembly Plus Raceways   |
| Other Features             | Single Row   With Flat Seat   |
| Long Description           | 20MM Bore 1; 20.2MM Bore 2; 37MM Outside Diameter; 12MM Height; Ball Bearing; Single Direction; Not |
| Inch – Metric              | Metric  |
| UNSPSC                     | 31171552  |
| Harmonized Tariff Code     | 8482.10.50.08   |
| Noun                       | Bearing   |

|                                     |                              |
|-------------------------------------|------------------------------|
| Keyword String                      | Ball Thrust                  |
| Manufacturer Item Number            | 2904                         |
| Weight / LBS                        | 0.15                         |
| Overall Height with Aligning Washer | 0 Inch   0 Millimeter        |
| Height                              | 0.472 Inch   12 Millimeter   |
| Bore 2                              | 0.795 Inch   20.2 Millimeter |
| Bore 1                              | 0.787 Inch   20 Millimeter   |
| D                                   | 1.457 Inch   37 Millimeter   |
| bore diameter:                      | 22 mm                        |
| static load capacity:               | 34700 N                      |
| outside diameter:                   | 42 mm                        |
| dynamic load capacity:              | 18900 N                      |
| overall width:                      | 14 mm                        |
| operating temperature range:        | -40 to 120 °C                |
| thrust bearing type:                | Single-Direction             |
| bearing material:                   | High Carbon Chrome Steel     |
| outside diameter design:            | Straight                     |
| cage material:                      | Steel                        |
| separable or banded:                | Separable                    |
| fillet radius:                      | 0.6 mm                       |
| precision rating:                   | ISO Class 0                  |
| manufacturer product page:          | <a href="#">Click here</a>   |