

NTN 81228 thrust ball bearings

Various types 168.275 mm db and sizes to accommodate 150 mm da your NTN 81228 thrust ball bearings requirements.

da	150 mm
db	168.275 mm
dc	146.05 mm
Da	269.999 mm
Ca	82.804 mm
A1	158.75 mm
A2	215.9 mm
S	4.763 mm
ba	65.088 mm
H	320.675 mm
H1	160.325 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/4 NPT
PG	1/4 NPT
h	50.8 mm
Housing	SAF 230

Bearing	22230 CC/W33
Lock nut	AN 30
Lock washer	W 30
Stabilizing ring	SR-30-0
Labyrinth ring (db shaft position)	LOR 151
PosiTrac Plus contact element (db shaft position)	B10724-151
Labyrinth ring (dc shaft position)	LOR 134
PosiTrac Plus contact element (dc shaft position)	B10724-134
End plug (suffix Y)	EPR 17
Max. speed for PosiTrac Plus seal	850 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	62.3 kN
Mass pillow block	82.3 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g