

NTN AC-6006LLU deep groove ball bearings

YOU'LL FIND AN EXTENSIVE 0.0 Inventory SELECTION OF NTN AC-6006LLU deep groove ball bearings FOR SALE. N/A Minimum Buy Quantity

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.77
EAN	7316577755575
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	YAR 205-015-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row Standard Duty Wide Inner Race Y Bearing Has Flinger

Long Description	2 Bolt Pillow Block; 15/16" Bore; 1-7/16" Base to Center Height; Set Screw Mount; Ball Bea
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 15/16 TF
Weight / LBS	1.7
d	23.812 mm
Nominal Bolt Center to Center	4.1 Inch 105 Millimeter
Bolt Spacing Maximum	4.344 Inch 110.338Millimeter
Bolt Spacing Minimum	3.688 Inch 93.675Millimeter
B	34.1 mm
Actual Bolt Center to Center	0 Inch 0Millimeter
D	1.344 Inch 34.13 Millimeter
Housing material	Cast iron
A	36 mm
A1	22 mm
A5	20.5 mm
B4	5 mm
H	70 mm
H1	36.5 mm
H2	16 mm
J	102 mm
J max.	110 mm
J min.	94 mm
L	130 mm
N	19.5 mm

N1	11.5 mm
s1	19.8 mm
RG	1/4-28 UNF
R1	2 mm
Rα	45 °
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	120 mm
J7	13 mm
N4	4 mm
Basic dynamic load rating C	14 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Limiting speed	7000 r/min
Mass bearing unit	0.74 kg
Thread grub screw G2	1/4-28 UNF
Hexagonal key size for grub screw N	3.175 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	SY 505 M
Bearing	YAR 205-015-2F
End cover	ECY 205