

NTN CRD-2252 tapered roller bearings

Browse 1,2 Outer Diameter (mm) NTN CRD-2252 tapered roller bearings Categories 4×1.2×1.8 Size (mm) 4 Bore Diameter (mm) in the Manufacturers Online Free. including .

Size (mm)	4×1.2×1.8
Bore Diameter (mm)	4
Outer Diameter (mm)	1,2
Width (mm)	1,8
d	1.2 mm
D	4 mm
B	1.8 mm
d1	2.15 mm
D1	3.05 mm
r1,2 – min.	0.1 mm
da – min.	2 mm
Da – max.	3.2 mm
ra – max.	0.1 mm
Basic dynamic load rating – C	0.062 kN
Basic static load rating – C0	0.016 kN
Fatigue load limit – Pu	0.001 kN
Reference speed	220000 r/min
Limiting speed	140000 r/min
Calculation factor – kr	0.02
Calculation factor – f0	6.4
d1 ≈	2.15 mm
D1 ≈	3.05 mm

r _{1,2} min.	0.1 mm
d _a min.	2 mm
D _a max.	3.2 mm
r _a max.	0.1 mm
Basic dynamic load rating C	0.062 kN
Basic static load rating C ₀	0.016 kN
Fatigue load limit P _u	0.001 kN
Calculation factor k _r	0.02
Calculation factor f ₀	6.4
Mass bearing	0.0001 kg