NTN CRD-6101 tapered roller bearings

Various types and 0.0 Inventory sizes to accommodate your NTN CRD-6101 tapered roller bearings requirements.

| Inventory | 0.0 |
|---------------------------|--|
| Manufacturer Name | ASAHI BEARINGS |
| Minimum Buy Quantity | N/A |
| Weight | 0.79 |
| EAN | 0808250122172 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Set Screw |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 3/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | UC205-15C4HR5 |
| Seals | Contact Seal |
| Housing Configuration | 1 Piece Solid |
| Inch — Metric | Inch |
| Other Features | Single Row Spherical Normal Duty High Temperature Range Up to 400 Degree F Has Slinger |

| Long Description | 2 Bolt Pillow Block; 15/16" Bore; 1-7/16" Base to Center Height; Set Screw Mount; Ball Bea |
|----------------------------------|---|
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | UCP205-15C4HR5 |
| Weight / LBS | 1.74 |
| В | 1.438 Inch 36.525 Millimeter |
| d | 0.938 Inch 23.825 Millimeter |
| Bolt Spacing Minimum | 3.75 Inch 95.25Millimeter |
| Nominal Bolt Center to Center | 4.1 Inch 105 Millimeter |
| Bolt Spacing Maximum | 4.5 Inch 114.3Millimeter |
| D | 1.339 Inch 34 Millimeter |
| Actual Bolt Center to Center | 0 Inch OMillimeter |