

NTN CRI-2416 tapered roller bearings

170 60 mm d Million used NTN CRI-2416 tapered roller bearings 22 mm B instantly searchable. Shop our large selection of parts based on brand, price, description, and location. Order the with stock ...

d	60 mm
D	110 mm
B	22 mm
E	100 mm
F	72 mm
d1	77.6 mm
rs min	1.5 mm
rls min	1.5 mm
Radial clearance class	CN
Mass (without HJ ring)	0.82 kg
Dynamic load, C	97.5 kN
Static load, C0	107 kN
Fatigue limit load, Cu	13 kN
Nlim (oil)	6,800 rpm
Nlim (grease)	5,800 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.98 Hz
Characteristic outer ring frequency, BPF0	6.7 Hz
Characteristic inner ring frequency, BRFI	9.3 Hz

da min	68 mm
dc min	80 mm
Da max	102 mm
ra max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.841
EAN	4547359134612
Product Group	B04144