

NTN CRI-3258 tapered roller bearings

100% Authentic. NTN CRI-3258 tapered roller bearings Highest Quality. 36,513 mm d Certified Supplier. 36,513 Bore Diameter (mm)

| | |
|-------------------------------|------------------|
| Bore Diameter (mm) | 36,513 |
| d | 36,513 mm |
| s1 | 29.4 mm |
| A1 | 13 mm |
| B1 | 38.9 mm |
| G | 12 mm |
| J | 92 mm |
| L | 118 mm |
| T | 50,4 mm |
| A2 | 13 mm |
| Weight | 1,45 Kg |
| Basic dynamic load rating (C) | 25,5 kN |
| Basic static load rating (C0) | 15,3 kN |
| Fatigue load limit (Pu) | 0,655 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.5 |
| EAN | 7316576614484 |
| Product Group | M06110 |
| Number of Mounting Holes | 4 |
| Mounting Method | Eccentric Collar |

| | |
|---------------------------------------|--|
| Housing Style | 4 Bolt Square Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 1/2 Inch |
| Relubricatable | Yes |
| Insert Part Number | YET 207-107 |
| Seals | M Seal |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |
| Long Description | 4 Bolt Square Flange Block; 1-7/16" Bore; 5.1" Bolt Circle; 3-5/8" Bolt Spacing; 1 Pi |
| Other Features | Single Row Standard Duty Narrow Inner Race Open End Y Bearing |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer Item Number | FY 1.7/16 FM |
| Weight / LBS | 3.31 |
| Bore | 1.438 Inch 36.525 Millimeter |
| Nominal Bolt Circle Diameter Round | 5.1 Inch 130 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |

| | |
|---|----------------------------------|
| Bolt Spacing | 3.625 Inch 92.08 Millimeter |
| Length Thru Bore | 1.531 Inch 38.9 Millimeter |
| Housing material | Cast iron |
| Da | 106.4 mm |
| Db1 | 87 mm |
| Db2 | 95 mm |
| A | 34.5 mm |
| A3 | 3.2 mm |
| A5 | 24.5 mm |
| N | 14 mm |
| RG | 1/4-28 UNF |
| R1 | 22.5 mm |
| DN | 6.5 mm |
| SWN | 7 mm |
| GN | 1/4-28 SAE-LT |
| J6 | 106 mm |
| J7 | 29 mm |
| N4 | 4 mm |
| Basic dynamic load rating C | 25.5 kN |
| Basic static load rating C0 | 15.3 kN |
| Fatigue load limit Pu | 0.655 kN |
| Limiting speed | 5300 r/min |
| Mass bearing unit | 1.3 kg |
| Thread grub screw G2 | 3/8-24 UNF |
| Hexagonal key size for grub screw N | 4.763 mm |
| Recommended tightening torque for grub screw | 16.5 N·m |

| | |
|---|-------------|
| Recommended diameter for attachment bolts, mm G | 12 mm |
| Recommended diameter for attachment bolts, inch G | 0.5 in |
| Housing | FY 507 M |
| Bearing | YET 207-107 |
| End cover | ECY 207 |