

NTN CRI-3266 tapered roller bearings

Our highly-skilled and 420 Outer Diameter (mm) factory-trained service experts 260 Bore Diameter (mm) have the resources 260x420x95 Size (mm) to help you with all your NTN CRI-3266 tapered roller bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

Size (mm)	260x420x95
Bore Diameter (mm)	260
Outer Diameter (mm)	420
Width (mm)	95
d	260 mm
D	420 mm
T	95 mm
d1	405 mm
r min.	5 mm
A	148 mm
B1	32 mm
B2	91 mm
C	45 mm
D1	329 mm
da min.	330 mm
Da max.	365 mm
ra max.	4 mm
Weight	51.5 Kg
Basic dynamic load rating (C)	1810 kN
Basic static load rating (C0)	7500 kN

Bore Type	Cylindrical Bore
Enclosure	Open
Configuration	Single Row
Bore Size	260 mm
Outside Diameter	420 mm
Fillet Radius/Chamfer	5 mm
Width	95 mm
Dynamic Load Rating	1,810,000 N
Static Load Rating	7,500,000 N
Limiting Speed – Oil	860 rpm
B	32 mm
da (min)	330 mm
Da (max)	365 mm
ra (max)	4 mm