

# NTN CRI-4027 tapered roller bearings

170 Million used 200 mm D NTN CRI-4027 tapered roller bearings instantly searchable. Shop our large selection of parts based on brand, price, 130 mm d description, and location. Order the with stock ...

d	130 mm
D	200 mm
B	33 mm
rs min	2 mm
Radial clearance class	C3
Mass	3.16 kg
Dynamic load, C	106 kN
Static load, C0	101 kN
Fatigue limit load, Cu	3.55 kN
f0	15.8
Nlim (grease)	3,200 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.87 Hz
Characteristic outer ring frequency, BPF0	6.56 Hz
Characteristic inner ring frequency, BRFI	8.44 Hz
da min	139 mm

Da max	191 mm
ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	3.27
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   I
Other Features	Deep Groove   Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	7.20911
Bore	5.118 Inch   130 Millimeter

Outside Diameter	7.874 Inch   200 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.299 Inch   33 Millimeter