

# NTN CRI-8403 tapered roller bearings

Welcome 0.0 Inventory to the NTN CRI-8403 tapered roller bearings online REXNORD Manufacturer Name seller.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 17.25  |
| EAN                       | 0662327116996  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22216LBC3  |
| Seals                     | Multi Labyrinth  |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 4 Bolt Pillow Block; 2-11/16" Bore; 3-1/2" Base to Center Height; Adapter Sleeve Mount; Sp |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | PLB6843FR                      |
| Manufacturer Internal Number  | 5811699                        |
| Weight / LBS                  | 38                             |
| Bolt Spacing Maximum          | 11 Inch   279.4Millimeter      |
| d                             | 2.688 Inch   68.275 Millimeter |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter   |
| B                             | 3.5 Inch   88.9 Millimeter     |
| Bolt Spacing Minimum          | 9.625 Inch   244.475Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| D                             | 0 Inch   0 Millimeter          |