

NTN E-M268749/M268710 tapered roller bearings

170 Million used NTN E-M268749/M268710 tapered roller bearings instantly searchable. Shop our large selection of 150 Bore Diameter (mm) parts based on 225 Outer Diameter (mm) brand, price, description, and location. Order the with 150x225x67.5 Size (mm) stock ...

Size (mm)	150x225x67.5
Bore Diameter (mm)	150
Outer Diameter (mm)	225
Width (mm)	67,5
d	150 mm
D	225 mm
H	67.5 mm
d1	184.9 mm
D1	206.2 mm
r1,2 – min.	2.1 mm
r3,4 – min.	1.1 mm
da – min.	161 mm
Da – max.	219 mm
ra – max.	2 mm
rb – max.	1 mm
dn	179.9 mm
Basic dynamic load rating – C	104 kN
Basic static load rating – C0	260 kN
Fatigue load limit – Pu	8 kN
Limiting speed for grease lubrication	4500 r/min

Limiting speed for oil lubrication	5300 mm/min
Preload class A	1300 N
Preload class B	3900 N
Static Axial rigidity, Preload class A	896 N/micron
Static Axial rigidity, Preload class B	1353 N/micron
Gref	80 cm
r _{1,2} min.	2.1 mm
r _{3,4} min.	1.1 mm
da min.	161 mm
Da max.	219 mm
ra max.	2 mm
rb max.	1 mm
Basic dynamic load rating C	104 kN
Basic static load rating C ₀	260 kN
Fatigue load limit P _u	8 kN
Attainable speed for grease lubrication	4500 r/min
Attainable speed for oil-air lubrication	5300 r/min
Static axial stiffnes for preload A	896 N/μm
Static axial stiffnes for preload B	1353 N/μm
Reference grease quantity Gref	80 cm ³
Mass bearing	9 kg