

NTN EE526130/526190 tapered roller bearings

NTN EE526130/526190 tapered roller bearings 170 mm Da Warehouse 67.793 mm Ca offers car 66.675 mm da parts and car accessories. We sell discount online as well as cheap machinery parts.

da	66.675 mm
Da	170 mm
Ca	67.793 mm
A1	98.425 mm
A2	160.338 mm
S	4.763 mm
ba	46.038 mm
H	209.55 mm
H1	107.95 mm
H2	44.45 mm
J min.	269.875 mm
J max.	320.675 mm
J1	53.975 mm
L	361.95 mm
N1	19.05 mm
R1	63.5 mm
R2	26.988 mm
RG	3/8 NPT
PG	1/8 NPT
h	42.862 mm
Housing	FSAF 616

Bearing	22316 EK
Adapter sleeve assembly	SNW 116×2.5/8
Stabilizing ring	SR-19-16
Labyrinth ring	2 x LOR 43
PosiTrac Plus contact element	2 x B10724-44
End plug (suffix Y)	EPR 8
Max. speed for PosiTrac Plus seal	2150 r/min
P60°	92.5 kN
P90°	55.6 kN
P120°	33.8 kN
P150°	30.7 kN
P180°	36.9 kN
Pa	14 kN
Mass pillow block	32.2 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	181.44 g