

NTN FL68/2,5ZZA deep groove ball bearings

YOU'LL FIND 105 Bore Diameter (mm) AN EXTENSIVE 105x160x26 Size (mm) SELECTION OF NTN FL68/2,5ZZA deep groove ball bearings 160 Outer Diameter (mm) FOR SALE.

| | |
|-------------------------------|---------------------------------|
| Size (mm) | 105x160x26 |
| Bore Diameter (mm) | 105 |
| Outer Diameter (mm) | 160 |
| Width (mm) | 26 |
| d | 105 mm |
| D | 160 mm |
| B | 26 mm |
| C | 26 mm |
| a | 3.71 mm |
| b | 3.1 mm |
| f | 2.82 mm |
| r min. | 2 mm |
| r1 min. | 0.5 mm |
| D1 | 155.22 mm |
| D2 | 169.7 mm |
| Weight | 1.54 Kg |
| Basic dynamic load rating (C) | 72,5 kN |
| Basic static load rating (C0) | 65,5 kN |
| (Grease) Lubrication Speed | 4000 r/min |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Enclosure | Snap Ring Groove with Snap Ring |

| | |
|----------------------------|-------------------|
| Bore Size | 105 mm |
| Outside Diameter | 160 mm |
| Width | 26 mm |
| Fillet Radius/Chamfer | 2 mm |
| r1 | 0.5 mm |
| Snap Ring Width | 2.8 mm |
| Snap Ring Outside Diameter | 169.7 mm |
| D1 (max) | 155.2 mm |
| a (max) | 3.7 mm |
| b (min) | 3.1 mm |
| Dynamic Load Rating | 72,500 N |
| Static Load Rating | 65,500 N |
| Limiting Speed – Grease | 4,000 rpm |
| Limiting Speed – Oil | 4,800 rpm |
| Factor fo | 15.8 |
| Radial Clearance | 0.015 to 0.041 mm |
| da (min) | 113 mm |
| Da (max) | 152 mm |
| Dx (min) | 172 mm |
| ra (max) | 2 mm |
| Cy (max) | 6.1 mm |