

NTN GK45X50X27S needle roller bearings

NTN GK45X50X27S needle roller bearings 95.809 mm Ca Needs Analysis 152.4 mm da , Manufacturing Service . Get Your Free.

da	152.4 mm
Da	309.999 mm
Ca	95.809 mm
A1	171.45 mm
A2	247.65 mm
S	4.763 mm
ba	74.612 mm
H	360.363 mm
H1	179.4 mm
H2	69.85 mm
L	628.65 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	54.769 mm
Housing	SSAFS 534
Bearing	22234 CCK/W33
Adapter sleeve assembly	SNW 34×6
Stabilizing ring	SR-34-0
Labyrinth ring	2 x LOR 141
End plug (suffix Y)	EPR 18
Bearing limiting speed	2600 r/min

P60°	345 kN
P90°	207 kN
P120°	127 kN
P150°	113 kN
P180°	133 kN
Pa	43.6 kN
Mass pillow block	168 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	878.85 g