

# NTN H961649/H961610G2 tapered roller bearings

We Provide 0.0 Inventory Extensive NTN H961649/H961610G2 tapered roller bearings Selection And Competitive Wholesale Pricing.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.49
EAN	7316576653889
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH2313 (Specify bore)
Withdrawal Nut	KM15
Inch – Metric	Metric
Long Description	65MM Tapered Bore; 140MM Outside Diameter; 48MM Width; C3-Loose Clearance; Adapter Mount; Double Row

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	7.687
D	5.512 Inch   140 Millimeter
d	2.559 Inch   65 Millimeter
Adapter Part Number	SNW113 H2313 HA2313 HE2313 (Specify Bore) Inch   H2313 (Specify bore) Millimeter
B	1.89 Inch   48 Millimeter
bore diameter:	65 mm
maximum rpm:	5000 RPM
outside diameter:	140 mm
operating temperature range:	Maximum of +390 °F
overall width:	48 mm
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	48 mm

dynamic load capacity:	340 kN
fillet radius:	2 mm
static load capacity:	360 kN
series:	223