

NTN HKS8X12X9M needle roller bearings

What are the types of NTN HKS8X12X9M needle roller bearings ?
 160.338 mm da Manufacturing 319.999 mm Da Service . Get Your Free, Instant price, design review.

da	160.338 mm
Da	319.999 mm
Ca	95.809 mm
A1	180.975 mm
A2	254 mm
S	4.763 mm
ba	75.406 mm
H	377.825 mm
H1	190.5 mm
H2	76.2 mm
L	679.45 mm
R1	114.3 mm
R2	41.275 mm
RG	3/4 NPT
PG	1/4 NPT
h	60.325 mm
Housing	SSAFS 536
Bearing	22236 CCK/W33
Adapter sleeve assembly	SNW 36×6.5/16
Stabilizing ring	SR-36-30
Labyrinth ring	2 x LOR 146
PosiTrac Plus contact element	2 x B10724-148

End plug (suffix Y)	EPR 19
Max. speed for PosiTrac Plus seal	875 r/min
P60°	535 kN
P90°	320 kN
P120°	196 kN
P150°	173 kN
P180°	202 kN
Pa	46.3 kN
Mass pillow block	197 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	1304.1 g