

# NTN HMK1212 needle roller bearings

Online shopping NTN HMK1212 needle roller bearings 71.438 mm da from a great selection at Store. ... Accessories.

da	71.438 mm
Da	180 mm
Ca	69.799 mm
A1	111.125 mm
A2	171.45 mm
ba	52.388 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	66.675 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	47.625 mm
Housing	FSAF 617
Bearing	1317 K
Adapter sleeve assembly	SNW 117×2.13/16
Stabilizing ring	2 x SR-1617

Labyrinth ring	2 x LOR 182
PosiTrac Plus contact element	2 x B10724-184
End plug (suffix Y)	EPR 10
Max. speed for PosiTrac Plus seal	1950 r/min
P60°	104 kN
P90°	62.3 kN
P120°	39.1 kN
P150°	35.6 kN
P180°	42.9 kN
Pa	10.5 kN
Mass pillow block	25.5 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	365.71 g