

# NTN HUB262-8 angular contact ball bearings

The online NTN HUB262-8 angular contact ball bearings parts N/A Minimum Buy Quantity store gives you immediate access to 0.0 Inventory a selection of more than 1.4 million new, used, remanufactured.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 10.442   |
| EAN                       | 0883450093521  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22215  |
| Seals                     | Double Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 4 Bolt Pillow Block; 3" Bore; 3-1/2" Base to Center Height; Eccentric Collar Mount; Spheri |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QMPX15J300SB                   |
| Weight / LBS                  | 28                             |
| D                             | 3.62 Inch   91.948 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| B                             | 3.5 Inch   88.9 Millimeter     |
| d                             | 3 Inch   76.2 Millimeter       |
| Bolt Spacing Minimum          | 9.06 Inch   230.124Millimeter  |
| Nominal Bolt Center to Center | 9.8 Inch   248.9 Millimeter    |
| Bolt Spacing Maximum          | 10.44 Inch   265.176Millimeter |