

# NTN K12X17X7.8 needle roller bearings

NTN K12X17X7.8 needle roller bearings Warehouse offers car parts and 25x52x15 Size (mm) car accessories. 25 Bore Diameter (mm) We sell discount online as well 52 Outer Diameter (mm) as cheap machinery parts.

|                               |              |
|-------------------------------|--------------|
| Size (mm)                     | 25x52x15     |
| Bore Diameter (mm)            | 25           |
| Outer Diameter (mm)           | 52           |
| Width (mm)                    | 15           |
| d                             | 25 mm        |
| D                             | 52 mm        |
| B                             | 15 mm        |
| C                             | 15 mm        |
| rn                            | 0,5 mm       |
| r min.                        | 1 mm         |
| da min.                       | 30 mm        |
| da max                        | 32 mm        |
| Da max.                       | 47 mm        |
| ra max.                       | 1 mm         |
| Weight                        | 0,128 Kg     |
| Basic dynamic load rating (C) | 14 kN        |
| Basic static load rating (C0) | 7,85 kN      |
| (Grease) Lubrication Speed    | 13 000 r/min |
| Inventory                     | 2.0          |
| Manufacturer Name             | NTN          |
| Minimum Buy Quantity          | N/A          |

|                                 |  |
|---------------------------------|--|
| Weight / Kilogram               | 0.13   |
| EAN                             | 4547359004601  |
| Product Group                   | B00308   |
| Enclosure                       | 2 Metal Shields  |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | No   |
| Rolling Element                 | Ball Bearing   |
| Snap Ring                       | No   |
| Internal Special Features       | No   |
| Cage Material                   | Steel  |
| Internal Clearance              | C0-Medium  |
| Inch – Metric                   | Metric   |
| Long Description                | 25MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO |
| Other Features                  | Deep Groove  |
| UNSPSC                          | 31171504   |
| Harmonized Tariff Code          | 8482.10.50.68  |
| Noun                            | Bearing  |
| Keyword String                  | Ball   |
| Manufacturer Item Number        | 6205ZZ   |
| Weight / LBS                    | 0.28   |
| Outer Race Width                | 0.591 Inch   15 Millimeter   |
| Bore                            | 0.984 Inch   25 Millimeter   |
| Outside Diameter                | 2.047 Inch   52 Millimeter   |
| Inner Race Width                | 0 Inch   0 Millimeter  |
| bore diameter:                  | 25 mm  |
| static load capacity:           | 7850 N   |
| outside diameter:               | 52 mm  |

|                              |                            |
|------------------------------|----------------------------|
| precision rating:            | ISO Class 0                |
| overall width:               | 15 mm                      |
| finish/coating:              | Uncoated                   |
| bore type:                   | Round                      |
| bearing material:            | High Carbon Chrome Steel   |
| closure type:                | Double Shielded            |
| cage material:               | Steel                      |
| row type & fill slot:        | Single Row Non-Fill Slot   |
| inner ring width:            | 15 mm                      |
| snap ring included:          | Without Snap Ring          |
| outer ring width:            | 15 mm                      |
| internal clearance:          | CN                         |
| maximum rpm (grease):        | 13000 rpm                  |
| operating temperature range: | -40 to 120 °C              |
| fillet radius:               | 1 mm                       |
| dynamic load capacity:       | 14000 N                    |
| manufacturer product page:   | <a href="#">Click here</a> |