

# NTN KJ40X45X22.3 needle roller bearings

Welcome to the NTN KJ40X45X22.3 needle roller bearings online 0.0 Inventory seller. TIMKEN Manufacturer Name

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 24.97  |
| EAN                       | 0883450152341  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 7/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22220  |
| Seals                     | Triple Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Double Nut   SAF Style  |
| Long Description          | 2 Bolt Pillow Block; 80MM Bore; 114.3MM Base to Center Height; V Lock Mount; Spherical Roller Bearin |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Weight / LBS                  | 65                              |
| d                             | 3.15 Inch   80 Millimeter       |
| Nominal Bolt Center to Center | 11.9 Inch   302.3 Millimeter    |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| B                             | 4.5 Inch   114.3 Millimeter     |
| D                             | 4.63 Inch   117.602 Millimeter  |
| Bolt Spacing Maximum          | 12.875 Inch   327.025Millimeter |
| Bolt Spacing Minimum          | 10.875 Inch   276.225Millimeter |