

NTN KJ45X50X29.6 needle roller bearings

What 25 mm d are the dimensions of a NTN KJ45X50X29.6 needle roller bearings? 25 Bore Diameter (mm) Manufacturing Service . Get Your Free, Instant Quote

Bore Diameter (mm)	25
d	25 mm
s1	19.8 mm
A	38 mm
A1	25 mm
B	34,1 mm
H	66 mm
H1	33 mm
H2	4 mm
J	95 mm
L	119 mm
N	11,2 mm
Thread (G)	10
Weight	0,38 Kg
Basic dynamic load rating (C)	14 kN
Basic static load rating (C0)	7,8 kN
Housing material	Pressed steel
B4	5 mm
Basic dynamic load rating C	14 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Permissible radial housing load max.	2.6 kN

Limiting speed	7000 r/min
Mass bearing unit	0.37 kg
Thread grub screw G2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	P 62
Bearing	YAR 205-2F
Rubber seating ring	RIS 205