

NTN KMJ15X21X16.8 needle roller bearings

NTN KMJ15X21X16.8 needle roller bearings Needs N/A Minimum Buy Quantity Analysis , Manufacturing Service . Get Your 0.0 Inventory Free.

| | |
|---------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 95 |
| EAN | 0013992049629 |
| Product Group | B04144 |
| Number of Mounting Holes | 4 |
| Mounting Method | Clamp Collar |
| Housing Style | 4 Bolt Round Flange Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-Expansion |
| Mounting Bolts | 24 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | MSE500BR |
| Seals | Triple Lip Labyrinth |
| Housing Configuration | 2 Piece Split |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |
| Long Description | 4 Bolt Round Flange Block; 5" Bore; 16.2" Bolt Circle; 2 Piece Split; Clamp Collar Mount; |

| | |
|---------------------------------------|---|
| Other Features | Single Row Wide Inner Ring Medium Duty |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Flanged |
| Weight / LBS | 209.24 |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Bolt Spacing | 11.5 Inch 291.3 Millimeter |
| d | 5 Inch 127 Millimeter |
| Nominal Bolt Circle Diameter Round | 16.2 Inch 412 Millimeter |
| D | 4.5 Inch 114.3 Millimeter |
| Shaft Size | 5 in |
| Seal Type | Aluminium Triple Labyrinth |
| Bearing Type | Split Cylindrical Retained Type |
| Support Type | Round Flange |
| Series Type | Medium Series |
| Bolt Size | 4 x M24 |
| Bearing – Housing – Seal | MSE500BRHATL |
| Bearing – Housing – Seal UPC | 013992042422 |
| Bearing UPC | 013992032751 |
| Dimension T | 18.5 in |
| Dimension R | 16.2 in |
| Dimension P | 1.0 in |
| Dimension H | 4.5 in |
| Dimension N | 13.625 in |
| Dimension V | 0.1 in |

| | |
|--------------------------|---|
| Dimension L | 8.1 in |
| Cr – Dynamic Load Rating | 118025 lbf |
| Cor – Static Load Rating | 157366 lbf |
| Ca – Axial Load Rating | 8588 lbf |
| Maximum Speed | 1600 rpm |
| Note | This product line was formerly known as “Revolvo” |