

NTN KXB090 angular contact ball bearings

Find the discount NTN KXB090 angular contact ball bearings online you need . We offer ... 160 Outer Diameter (mm) If you check out our large selection of NTN KXB090 angular contact ball bearings once 240x160x38 Size (mm) .

Size (mm)	240x160x38
Bore Diameter (mm)	240
Outer Diameter (mm)	160
Width (mm)	38
d	160 mm
D	240 mm
B	38 mm
D1	210.8 mm
F	180 mm
r1,2 – min.	2.1 mm
r3,4 – min.	1.5 mm
s	5.2 mm
da – min.	167 mm
da – max.	177 mm
db – min.	183 mm
Da – max.	230 mm
ra – max.	2 mm
rb – max.	1.5 mm
Basic dynamic load rating – C	229 kN
Basic static load rating – C0	325 kN
Fatigue load limit – Pu	35.5 kN

Reference speed	3000 r/min
Limiting speed	4800 r/min
Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	6.075
EAN	7316571293677
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	160MM Bore; Straight Bore Profile; 240MM Outside Diameter; 38MM Width; Brass Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00

Noun	Bearing
Manufacturer Item Number	NU 1032 ML
Weight / LBS	13.382
Width	1.496 Inch 38 Millimeter
Bore	6.299 Inch 160 Millimeter
Outside Diameter	9.449 Inch 240 Millimeter
D1 ≈	210.8 mm
r1,2 min.	2.1 mm
r3,4 min.	1.5 mm
s max.	5.2 mm
da min.	167 mm
da max.	177 mm
db min.	183 mm
Da max.	230 mm
ra max.	2 mm
rb max.	1.5 mm
Basic dynamic load rating C	229 kN
Basic static load rating C0	325 kN
Fatigue load limit Pu	35.5 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	5.98 kg
Angle ring	HJ 1032