

NTN

LM287649D/LM287610/LM287610DG 2 tapered roller bearings

NTN LM287649D/LM287610/LM287610DG2 tapered roller bearings
Needs NTN Manufacturer Name Analysis , N/A Minimum Buy
Quantity 5.0 Inventory Manufacturing Service . Get Your Free.

Inventory	5.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	2.02
EAN	4547359579246
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	65MM Bore; 140MM Outside Diameter; 33MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 IS
Other Features	Deep Groove Electric Motor Grade

UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6313ZZC3/EM
Weight / LBS	4.453
d	2.559 Inch 65 Millimeter
D	5.512 Inch 140 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.299 Inch 33 Millimeter
bore diameter:	65 mm
precision rating:	ISO Class 0
outside diameter:	140 mm
finish/coating:	Uncoated
overall width:	33 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	33 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	33 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	4900 rpm
internal clearance:	C3
fillet radius:	2.1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	5800 RPM
dynamic load capacity:	92500 N

series:	63
static load capacity:	60000 N
manufacturer product page:	Click here