

# NTN LM767749D/LM767710+A tapered roller bearings

The online NTN LM767749D/LM767710+A tapered roller bearings parts store gives you immediate access to a selection 180 mm Da of more than 1.4 million new, used, remanufactured. 88.9 mm da

|         |            |
|---------|------------|
| da      | 88.9 mm    |
| Da      | 180 mm     |
| Ca      | 55.804 mm  |
| A1      | 111.125 mm |
| A2      | 222.25 mm  |
| S       | 4.763 mm   |
| ba      | 44.45 mm   |
| H       | 217.488 mm |
| H1      | 114.3 mm   |
| H2      | 44.45 mm   |
| J min.  | 295.275 mm |
| J max.  | 333.375 mm |
| J1      | 60.325 mm  |
| L       | 387.35 mm  |
| N1      | 22.225 mm  |
| R1      | 58.737 mm  |
| R2      | 30.163 mm  |
| RG      | 3/8 NPT    |
| PG      | 1/4 NPT    |
| h       | 42.069 mm  |
| Housing | FSAF 520   |

|  |                |
|--|----------------|
| Bearing                                | 22220 EK       |
| Adapter sleeve assembly                | SNW 20×3.1/2   |
| Stabilizing ring                       | SR-20-17       |
| Taconite seal                          | TER 103        |
| End plug (suffix Y)                    | EPR 15         |
| Max. speed for Taconite seal           | 900 r/min      |
| P60°                                   | 119 kN         |
| P90°                                   | 71.2 kN        |
| P120°                                  | 44.5 kN        |
| P150°                                  | 40 kN          |
| P180°                                  | 48.9 kN        |
| Pa                                     | 13.8 kN        |
| Mass pillow block                      | 28.1 kg        |
| Cap bolt                               | 2 x 3/4-10 UNC |
| Cap bolt recommended tightening torque | 203.4 N·m      |
| Cap bolt, SAE grade                    | 5              |
| Appropriate attachment bolt size G     | 0.75 in        |
| Initial grease fill                    | 181.44 g       |