## NTN NA4903LL needle roller bearings

How do I place an EMERGENCY order for a NTN NA4903LL needle roller bearings that I 0.0 Inventory want N/A Minimum Buy Quantity to pick up at a our store?

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 4.086   |
| EAN                       | 0883450294331   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22209   |
| Seals                     | Double Lip Viton  |
| Housing Configuration     | 1 Piece Solid   |
| Inch — Metric             | Metric  |
| Other Features            | Double Row  |
| Long Description          | 2 Bolt Pillow Block; 40MM Bore;<br>57.2MM Base to Center Height;<br>Eccentric Collar Mount;<br>Spherical Roll |

|                                  | 1                             |
|----------------------------------|-------------------------------|
| UNSPSC                           | 31171511                      |
| Harmonized Tariff Code           | 8483.20.40.80                 |
| Noun                             | Bearing                       |
| Keyword String                   | Pillow Block                  |
| Manufacturer Item Number         | QMP09J040SEC                  |
| Weight / LBS                     | 10                            |
| d                                | 1.575 Inch   40 Millimeter    |
| Nominal Bolt Center to<br>Center | 6.7 Inch   170 Millimeter     |
| В                                | 2.252 Inch   57.2 Millimeter  |
| D                                | 2.875 Inch   73.02 Millimeter |
| Bolt Spacing Maximum             | 7.12 Inch   180.848Millimeter |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter          |
| Bolt Spacing Minimum             | 6.25 Inch   158.75Millimeter  |
| Bolt Spacing Minimum             | 6.25 Inch   158.75Millimeter  |