

NTN NA4920S needle roller bearings

NTN NA4920S needle roller bearings SEARCH 190 mm Da – Whether it's 73.787 mm Ca agriculture or construction equipment your working on, Has the you need. 77.787 mm da

da	77.787 mm
Da	190 mm
Ca	73.787 mm
A1	111.125 mm
A2	231.775 mm
S	4.763 mm
ba	52.388 mm
H	230.981 mm
H1	120.65 mm
H2	50.8 mm
J min.	304.8 mm
J max.	342.9 mm
J1	57.15 mm
L	393.7 mm
N1	22.225 mm
R1	73.025 mm
R2	28.575 mm
RG	3/8 NPT
PG	1/8 NPT
h	47.625 mm
Housing	SAF 618
Bearing	22318 EK

Adapter sleeve assembly	SNW 118×3.1/16
Stabilizing ring	SR-21-18
Taconite seal	TER 186
End plug (suffix Y)	EPR 11
Max. speed for Taconite seal	950 r/min
P60°	128 kN
P90°	77 kN
P120°	48.9 kN
P150°	44.5 kN
P180°	54.3 kN
Pa	17.3 kN
Mass pillow block	44 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g