

NTN NJ1010 cylindrical roller bearings

NTN NJ1010 cylindrical roller bearings Product Brochures , 0.0 Inventory Manufacturing Service . SKF Manufacturer Name Get Your Free.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	308.669
EAN	7316577118707
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Tapered Adapter Sleeve
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Steel
Expansion / Non-expansion	Expansion
Mounting Bolts	1-1/2 Inch
Relubricatable	Yes
Insert Part Number	22244 CCK/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Double Row Heavy Duty
Long Description	4 Bolt Pillow Block; 7-15/16" Bore; 9-1/2" Base to Center Height; Tapered Adapter Sleeve M

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAFS 22544
Weight / LBS	577
Bolt Spacing Maximum	27.875 Inch 708.025Millimeter
Nominal Bolt Center to Center	26.3 Inch 668.3 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Minimum	24.75 Inch 628.65Millimeter
B	9.5 Inch 241.3 Millimeter
D	12 Inch 304.8 Millimeter
d	7.938 Inch 201.625 Millimeter
da	201.613 mm
Da	399.999 mm
Ca	117.805 mm
A1	222.25 mm
A2	311.15 mm
S	4.763 mm
ba	90.487 mm
H	473.075 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm

R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	79.375 mm
Housing	SAFS 544
Bearing	22244 CCK/W33
Adapter sleeve assembly	SNW 44×7.15/16
Stabilizing ring	SR-44-38
Labyrinth ring	2 x LOR 167
End plug (suffix Y)	EPR 23
Bearing limiting speed	2000 r/min
P60°	691 kN
P90°	414 kN
P120°	260 kN
P150°	236 kN
P180°	285 kN
Pa	71.2 kN
Mass pillow block	356 kg
Cap bolt	1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g