## NTN NK10X59X30.5 needle roller bearings

High Quality NTN NK10X59X30.5 needle roller bearings. Competitive Pricing. Accept Small Order. Easy 0.0 Inventory and Fast Shipping.

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.35  |
| EAN                       | 0793699323092   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Flange Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | MB25-58-HFFPA   |
| Seals                     | Free Running HFF  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch — Metric             | Inch  |
| Long Description          | 2 Bolt Flange Block; 5/8"<br>Bore; 3" Bolt Circle; 3" Bolt<br>Spacing; 1 Piece Solid; Set S |

| Other Features                        | Single Row   Standard Duty  <br>10% Oil Fill   Flingers Only |
|---------------------------------------|--|
| UNSPSC                                | 31171501   |
| Harmonized Tariff Code                | 8483.20.40.40  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | FC225-58-HFF   |
| Manufacturer Internal Number          | 0132309  |
| Weight / LBS                          | 0.77   |
| d                                     | 0.625 Inch   15.875<br>Millimeter                            |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter  |
| Nominal Bolt Circle Diameter<br>Round | 3 Inch   76 Millimeter                                       |
| D                                     | 0.984 Inch   25 Millimeter                                   |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter  |
| Bolt Spacing                          | 3 Inch   76.2 Millimeter                                     |