

# NTN NK165/42 needle roller bearings

Browse NTN NK165/42 needle roller bearings Categories ABB MOTORS AND MECHANICAL INC Manufacturer Name in 0.0 Inventory the Manufacturers Online Free. including .

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 36.32  |
| EAN                       | 0782475036134  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Tapered Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | S1U-SD-212   |
| Seals                     | Dual Piston Ring Seal  |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Special Duty  |
| Long Description          | 2 Bolt Pillow Block; 2-3/4" Bore; 4-3/4" Base to Center Height; Tapered Adapter Sleeve Mou |

|                               |                               |
|-------------------------------|-------------------------------|
| UNSPSC                        | 31171511                      |
| Harmonized Tariff Code        | 8483.20.40.80                 |
| Noun                          | Bearing                       |
| Keyword String                | Pillow Block                  |
| Manufacturer Item Number      | P2B-SD-212E SPECIAL DUTY      |
| Manufacturer Internal Number  | 066263                        |
| Weight / LBS                  | 80                            |
| d                             | 2.75 Inch   69.85 Millimeter  |
| B                             | 4.75 Inch   120.65 Millimeter |
| Bolt Spacing Maximum          | 12.5 Inch   317.5Millimeter   |
| D                             | 5.75 Inch   146.05 Millimeter |
| Nominal Bolt Center to Center | 11.8 Inch   300 Millimeter    |
| Bolt Spacing Minimum          | 11 Inch   279.4Millimeter     |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter          |